

**Achieving Load Reductions through Large-Scale Implementations of Stormwater Controls in Kansas City and Cincinnati**

**(or: Is it possible to achieve discharge objectives in large areas by retro-fitting stormwater controls?)**

Robert Pitt, PE, Ph.D., BCEE, D.WRE,  
Leila Talebi, Ph.D.

2014; 10th Annual California Stormwater Quality Association (CASQA) Conference; September 2014; Orange County, CA

1


**Questions to be Addressed in Presentation**

- How effective are source area controls in reducing outfall discharges?
- Can individual device data be extrapolated to system scales?
- How do you ensure high levels of performance at the system level?
- How do you monitor system to verify performance?
- How much information is necessary to verify performance?


2

**Kansas City's CSO Challenge**

- Combined sewer area: 58 mi<sup>2</sup>
- Fully developed
- Rainfall: 37 in./yr
- 36 sewer overflows/yr by rain > 0.6 in; reduce frequency by 65%.
- 6.4 billion gal overflow/yr, reduce to 1.4 billion gal/yr
- Aging wastewater infrastructure
- Sewer backups
- Poor receiving-water quality



3




4


### Summary of Constructed Stormwater Controls in Test Area

Design plan component	Number of this type of stormwater control units in 100 acre test (pilot) area	Device as a % of the drainage area	Average drainage area for each unit (ac)	Total area treated by these devices (ac)
Bioretention	24 (no curb extensions)	1.6	0.40	9.6
	28 (with curb extension)	1.5	0.40	11.2
	5 (shallow)	1.6	0.40	2.0
Bioswale	1 (vegetated swale)	8.9	0.50	0.5
Cascade	5 (terraced bioretention cells in series)	1.9	0.40	2.0
Porous sidewalk or pavement	18 (with underdrains)	100.0	0.015	0.3
	5 (with underground storage cubes)	99.9	0.015	0.1
Rain garden	64 (no curb extensions)	2.8	0.40	25.6
	8 (with curb extension)	1.5	0.40	3.2

5




6




7




8




9




10




11



12




13




14




15




16




17




18




19




20



21




22




23




24




25



26



27



28

Performance Monitoring at Cincinnati Stormwater Control Sites	
Location	Runoff Volume Reduction (%) Compared to Pre-Construction Data
Cincinnati State College – Southern Area (bioinfiltration and rain gardens)	80
Cincinnati Zoo – Main Entrance (extensive paver blocks)	Average Rv values after construction: 0.1 (compared to about 0.8 for conventional pavement in area)
Cincinnati Zoo – African Savannah (rainwater harvesting system and pavement removal)	70
Clark Montessori High School (green roofs and parking lot biofilters on small portion of watershed)	21

29

### Conclusions and Recommendations for Flow Monitoring for Large-Scale Stormwater Control Performance Verification

- Monitor both test and control areas both before and after construction of stormwater controls, if possible, for the greatest reliability (to account for typical year-to-year rainfall variations and to detect sensor problems early).
- Test areas should have most of their flows treated by the control practices to maximize measurable reductions.
  - **Any untreated upgradient areas should be very small in comparison to the test areas. Difficult to subtract two large numbers (each having measurement errors and other sources of variability), such as above and down gradient monitoring stations, and have confidence on the targeted flows.**

30


### Conclusions and Recommendations for Flow Monitoring for Large-Scale Stormwater Control Performance Verification (Cont.)

- Most monitored flows from common rains may only result in shallow water depths in the sewerage, a flow condition that is difficult to accurately monitor.
- Flow sensors may fail more often than expected.
- Costs of flow monitoring is small compared to green infrastructure investment.
  - **Use redundant sensors, such as an area-velocity sensor (or bubbler) in addition to an acoustic depth sensor mounted on the crown.**
  - **Calibrate the flow sensors at the beginning and periodically throughout the project period and use weirs.**
  - **Review flow data frequently and completely to identify sensor failures or other issues.**
  - **Supplement the flow sensors with adequate numbers and placement of rain gages in the watersheds.**

31

### Conclusions and Recommendations for Flow Monitoring for Large-Scale Stormwater Control Performance Verification (Cont.)

- Monitor sufficient numbers of events to have statistically valid results for the performance expectations.
  - **As an example, with a COV approaching 1 (a typical value for stormwater), 50 pairs of samples would enable differences of about 50% or greater to be detected with 95% confidence and 80% power.**
  - **It is very difficult to detect small differences with suitable confidence and power (the reason why most of the runoff needs to be treated).**



32