



Project Summary

Potential Groundwater Contamination from Intentional and Nonintentional Stormwater Infiltration

Robert Pitt, Shirley Clark, and Keith Parmer

The research summarized here was conducted during the first year of a 3-yr cooperative agreement to identify and control stormwater toxicants, especially those adversely affecting groundwater. The purpose of this research effort was to review the groundwater contamination literature as it relates to stormwater. Potential problem pollutants were identified, based on their mobility through the unsaturated soil zone above groundwater, their abundance in stormwater, and their treatability before discharge. This information was used with earlier EPA research results to identify the possible sources of these potential problem pollutants. Recommendations were also made for stormwater infiltration guidelines in different areas and monitoring that should be conducted to evaluate a specific stormwater for its potential to contaminate groundwater.

This Project Summary was developed by EPA's Risk Reduction Engineering Laboratory, Cincinnati, OH, to announce key findings of the research project that is fully documented in a separate report of the same title (see Project Report ordering information at back).

Introduction

Before urbanization, groundwater was recharged by precipitation infiltrating through pervious surfaces, including grasslands and woods. This infiltrating water was relatively uncontaminated. Urbaniza-

tion, however, reduced the permeable soil surface area through which recharge by infiltration could occur. This resulted in much less groundwater recharge and greatly increased surface runoff. In addition, the waters available for recharge generally carried increased quantities of pollutants. With urbanization, waters having elevated contaminant concentrations also recharge groundwater, including effluent from domestic septic tanks, wastewater from percolation basins and industrial waste injection wells, infiltrating stormwater, and infiltrating water from agricultural irrigation. This report addresses potential groundwater problems associated with stormwater toxicants and describes how conventional stormwater control practices can reduce these problems.

Sources of Pollutants

High bacteria populations have been found in sheetflow samples from sidewalks, roads, and some bare ground (collected from locations where dogs would most likely be "walked"). Tables 1 and 2 summarize toxicant concentrations and likely sources or locations having some of the highest concentrations found during an earlier phase of this EPA-funded research. The detection frequencies for the heavy metals are all close to 100% for all source areas, and the detection frequencies for the organics listed on these tables ranged from about 10% to 25%. Vehicle service areas had the greatest abundance of observed organics.



Table 1. Concentrations of Heavy Metals in Observed Areas ($\mu\text{g/L}$)

Toxicant	Highest Median		Highest Observed	
Cadmium	Vehicle service area runoff	8	Street runoff	220
Chromium	Landscaped area runoff	100	Roof runoff	510
Copper	Urban receiving water	160	Street runoff	1250
Lead	CSO	75	Storage area runoff	330
Nickel	Parking area runoff	40	Landscaped area runoff	130
Zinc	Roof runoff	100	Roof runoff	1580

Table 2. Maximum Concentrations of Toxic Organics from Observed Sources

Toxicant	Maximum, $\mu\text{g/L}$	Detection Frequency, %	Significant Sources
Benzo (a) anthracene	60	12	Gasoline, wood preservative
Benzo (b) fluoranthene	226	17	Gasoline, motor oils
Benzo (k) fluoranthene	221	17	Gasoline, bitumen, oils
Benzo (a) pyrene	300	17	Asphalt, gasoline, oils
Fluoranthene	128	23	Oils, gasoline, wood preservative
Naphthalene	296	13	Coal tar, gasoline, insecticides
Phenanthrene	69	10	Oils, gasoline, coal tar
Pyrene	102	19	Oils, gasoline, bitumen, coal tar, wood preservative
Chlordane	2.2	13	Insecticide
Butyl benzyl phthalate	128	12	Plasticizer
Bis (2-chloroethyl) ether	204	14	Fumigant, solvents, insecticides, paints, lacquers, varnishes
Bis (2-chloroisopropyl) ether	217	14	Pesticide manufacturing
1,3-Dichlorobenzene	120	23	Pesticide manufacturing

Stormwater Constituents Having High Potential to Contaminate Groundwater

Nutrients

Nitrates are one of the most frequently encountered contaminants in groundwater. Phosphorus contamination of groundwater has not been as widespread, or as severe, as that of nitrogen compounds. Whenever nitrogen-containing compounds come into contact with soil, a potential exists for nitrate leaching into groundwater, especially in rapid-infiltration wastewater basins, stormwater infiltration devices, and agricultural areas. Nitrate has leached from fertilizers and affected groundwaters under various turf grasses in urban areas, including golf courses, parks, and home lawns. Significant leaching of nitrates occurs during the cool, wet seasons. Cool temperatures reduce denitrification and ammonia volatilization and limit microbial nitrogen immobilization and plant uptake. The use of slow-release fertilizers (including composted organic mulches, urea formaldehyde (UF), methylene urea, isobutylidene diurea (IBDU), and sulfur-coated urea) is recommended

in areas having potential groundwater nitrate problems.

Residual concentrations of nitrate in soil vary greatly and depend on the soil texture, mineralization, rainfall and irrigation patterns, organic matter content, crop yield, nitrogen fertilizer/sludge application rate, denitrification, and soil compaction. Nitrate is highly soluble ($>1 \text{ kg/L}$) and will stay in solution in the percolation water. If it leaves the root zone without being taken-up by plants, it will readily reach the groundwater.

Pesticides

Urban pesticide contamination of groundwater can result from municipal and homeowner use for pest control and the subsequent collection of the pesticide in stormwater runoff. Pesticides that have been found in urban groundwaters include: 2,4-D, 2,4,5-T, atrazine, chlordane, diazinon, ethion, malathion, methyl trithion, silvex, and simazine. Heavy repetitive use of mobile pesticides (those that are not likely to be retained by various processes in the soil before they reach the groundwater, such as 2,4-D, acenaphthylene, alachlor, atrazine, cyanazine, dacthal,

diazinon, dicamba, and malathion) on irrigated and sandy soils will likely contaminate groundwater. Fungicides and nematocides must be mobile to reach the target pest, and hence, they generally have the highest groundwater contamination potential. Pesticide leaching depends on patterns of use, soil texture, total organic carbon content of the soil, pesticide persistence, and depth to the water table.

The greatest pesticide mobility occurs in areas with coarse-grained or sandy soils without a hardpan layer, and with soils that have low clay and organic matter content and high permeability. Structural voids, generally found in the surface layer of finer-textured soils rich in clay, can transmit pesticides rapidly when the voids are filled with water and the adsorbing surfaces of the soil matrix are bypassed. In general, pesticides with low water solubilities, high octanol-water partitioning coefficients, and high carbon partitioning coefficients are less mobile. The slower moving pesticides that may better sorb to soils have been recommended for use in areas of groundwater contamination concern. These include the fungicides iprodione and triadimefon, the insecticides isofenphos and chlorpyrifos, and the herbicide glyphosate.

Pesticides decompose in soil and water, but the total decomposition time can range from days to years. Literature half-lives for pesticides generally apply to surface soils and do not account for the reduced microbial activity found deep in the vadose zone. Pesticides with a 30-day half life can show considerable leaching. An order-of-magnitude difference in half-life results in a five- to ten-fold difference in percolation loss. Organophosphate pesticides are less persistent than organochlorine pesticides, but they also are not strongly adsorbed by the sediment and are likely to leach into the vadose zone and the groundwater.

Other Organics

The most commonly occurring organic compounds found in urban groundwaters include phthalate esters (especially bis(2-ethylhexyl)phthalate) and phenolic compounds. Other, more rarely found, organics include the volatiles: benzene, chloroform, methylene chloride, trichloroethylene, tetrachloroethylene, toluene, and xylene. Polycyclic aromatic hydrocarbons (PAHs) (especially benzo(a)anthracene, chrysene, anthracene, and benzo(b)fluoranthene) have also been found in groundwaters near industrial sites.

Groundwater contamination from organics, like that from other pollutants, occurs

more readily in areas with sandy soils and where the water table is near the land surface. Organics can be removed from the soil and recharge water by volatilization, sorption, and degradation. Volatilization can significantly reduce the concentrations of the most volatile compounds in groundwater, but the rate of gas transfer from the soil to the air is usually limited by the presence of soil water. Hydrophobic sorption onto soil organic matter limits the mobility of less soluble base/neutral and acid extractable compounds through organic soils and the vadose zone. Sorption is not always a permanent removal mechanism, however. Organic resolubilization can occur during wet periods following dry periods. Many organics can be degraded by microorganisms, at least partially, but others cannot. Temperature, pH, moisture content, ion exchange capacity of the soil, and air availability may limit the microbial degradation potential for even the most degradable organic compound.

Microorganisms

Viruses have been detected in groundwater where stormwater recharge basins were located short distances above the aquifer. Enteric viruses are more resistant to environmental factors than are enteric bacteria, and they exhibit longer survival times in natural waters. They can occur in potable and marine waters in the absence of fecal coliforms. Enteroviruses are also more resistant to commonly used disinfectants than are indicator bacteria (such as fecal coliforms), and they can occur in groundwater in the absence of indicator bacteria.

The factors that affect the survival of enteric bacteria and viruses in the soil include pH, antagonism from soil microflora, moisture content, temperature, sunlight, and organic matter. The two most important attributes of viruses that permit their long-term survival in the environment are their structure and very small size. These characteristics permit virus occlusion and protection within colloid-size particles. Viral adsorption is promoted by increasing cation concentration, decreasing pH, and decreasing soluble organics. Since the movement of viruses through soil to groundwater occurs in the liquid phase and involves water movement and associated suspended virus particles, the distribution of viruses between the adsorbed and liquid phases determines the viral mass available for movement. Once the virus reaches the groundwater, it can travel laterally through the aquifer until it is either adsorbed or inactivated.

The major bacterial removal mechanisms in soil are straining at the soil surface and at intergrain contacts, sedimentation, sorption by soil particles, and inactivation. Because their size is larger than viruses, most bacteria are retained near the soil surface because of this straining effect. In general, enteric bacteria survive in soil between 2 and 3 mo, although survival times up to 5 yr have been documented.

Metals

From a groundwater pollution standpoint, the metals in stormwater presenting the most environmental concern are aluminum, arsenic, cadmium, chromium, copper, iron, lead, mercury, nickel, and zinc. The majority of these metals (with the common exception of zinc) are, however, mostly associated with the particulate fractions and can be mostly removed by either sedimentation or filtration processes.

In general, studies of recharge basins receiving large metal loads found that most of the heavy metals are removed either in the basin sediment or in the vadose zone. Dissolved metal ions are removed from stormwater during infiltration mostly by adsorption onto the near-surface particles in the vadose zone, and the particulate metals are filtered out at the soil surface. Studies at recharge basins found that lead, zinc, cadmium, and copper accumulated at the soil surface with little downward movement over many years. At a commercial site, however, nickel, chromium, and zinc concentrations have exceeded regulatory limits in the soils below a recharge area. Allowing percolation ponds to go dry between storms can be counterproductive to the removal of lead from the water during recharge. Apparently, the adsorption bonds between the sediments and the metals can be weakened during the drying period.

Similarities in water quality between runoff water and groundwater have shown that there is significant downward movement of copper and iron in sandy and loamy soils. Arsenic, nickel, and lead, however, did not significantly move downward through the soil to the groundwater. The exception to this was some downward movement of lead with the percolation water in sandy soils beneath stormwater recharge basins. Zinc, which is more soluble than iron, has been found in higher concentrations in groundwater than iron. The order of attenuation in the vadose zone from infiltrating stormwater is: zinc (most mobile) > lead > cadmium > manganese > copper > iron > chromium > nickel > aluminum (least mobile).

Salts

Salt applications for winter traffic safety is a common practice in many northern areas, and the sodium and chloride, which are collected in the snowmelt, travel down through the vadose zone to the groundwater with little attenuation. Soil is not very effective at removing salts. Salts that are still in the percolation water after it travels through the vadose zone will contaminate the groundwater. Infiltrating stormwater has increased sodium and chloride concentrations above background concentrations. Fertilizer and pesticide salts also accumulate in urban areas and can leach through the soil to the groundwater.

Studies of depth of pollutant penetration in soil have shown that sulfate and potassium concentrations decrease with depth, whereas sodium, calcium, bicarbonate, and chloride concentrations increase with depth. Once contamination with salts begins, the movement of salts into the groundwater can be rapid. The salt concentration may not lessen until the source of the salts is removed.

Treatment of Stormwater

Table 3 summarizes the filterable fraction of toxicants found in runoff sheet flows from many urban areas found during an earlier phase of this EPA-funded research. Pollutants that are mostly in filterable forms have a greater potential of affecting groundwater and are more difficult to control with the use of conventional stormwater control practices which mostly rely on sedimentation and filtration principles. Luckily, most of the toxic organics and metals are associated with the nonfilterable (suspended solids) fraction of the wastewaters during wet weather. Possible exceptions include zinc, fluoranthene, pyrene, and 1,3-dichlorobenzene, which may be mostly found in the filtered sample portions. Pollutants in dry-weather storm drainage flows, however, tend to be much more associated with filtered sample fractions and would not be as readily controlled with the use of sedimentation.

Sedimentation is the most common fate and control mechanism for particulate-related pollutants. This would be common for most stormwater pollutants, as noted above. Particulate removal can occur in many conventional stormwater control processes, including catchbasins, screens, drainage systems, and detention ponds. Sorption of pollutants onto solids and metal precipitation increases the sedimentation potential of these pollutants and also encourages more efficient bonding of the pollutants in soils to prevent their leaching

Table 3. Reported Filterable Fractions of Stormwater Toxicants from Source Areas

Constituent	Filterable Fraction (%)
Cadmium	20 to 50
Chromium	<10
Copper	<20
Iron	Small amount
Lead	<20
Nickel	Small amount
Zinc	>50
Benzo (a) anthracene	None found in filtered fraction
Fluoranthene	65
Naphthalene	25
Phenanthrene	None found in filtered fraction
Pyrene	95
Chlordane	None found in filtered fraction
Butyl benzyl phthalate	Irregular
Bis (2-chloroethyl) ether	Irregular
Bis (2-chloroisopropyl) ether	None found in filtered fraction
1,3-Dichlorobenzene	75

to groundwaters. Detention ponds are probably the most common management practice for the control of stormwater runoff. If properly designed, constructed, and maintained, wet detention ponds can be very effective in controlling a wide range of pollutants. The monitored performance of wet detention ponds indicates more than 90% removal for suspended solids, 70% for BOD₅ and COD, about 60% to 70% for nutrients, and about 60% to 95% for heavy metals. Catchbasins are very small sedimentation devices. Adequate cleaning can help reduce the total solids and lead urban runoff yields by between 10% and 25%, and COD, total Kjeldahl nitrogen, total phosphorus, and zinc by between 5% and 10%. Other important fate mechanisms available in wet detention ponds, but which are probably not important in small enclosed sump devices such as catchbasins, include volatilization and photolysis. Biodegradation, biotransformation, and bioaccumulation (into plants and animals) may also occur in larger and open ponds.

Upland infiltration devices (such as infiltration trenches, porous pavements, percolation ponds, and grass roadside drainage swales) are located at urban source areas. Infiltration (percolation) ponds are usually located at stormwater outfalls or at large paved areas. These basins, along with perforated storm sewers, can infiltrate flows and pollutants from all upland sources combined. Infiltration devices can safely deliver large fractions of the surface flows to groundwater, if carefully designed and located. Local conditions that can make stormwater infiltration inappropriate include steep slopes, slowly percolating soils, shallow groundwater, and nearby groundwater uses.

Grass filter strips may be quite effective in removing particulate pollutants from overland flows. The filtering effects of grasses, along with increased infiltration/recharge, reduce the particulate sediment load from urban landscaped areas. Grass swales are another type of infiltration device and can be used in place of curb and gutter drainages in most land uses, except possibly strip commercial and high density residential areas. Grass swales allow the recharge of significant amounts of surface flows. Swales can also reduce pollutant concentrations because of filtration. Soluble and particulate heavy metal (copper, lead, zinc, and cadmium) concentrations can be reduced by at least 50%, COD, nitrate nitrogen, and ammonia nitrogen concentrations can be reduced by about 25%, but only inconsistent concentration reductions can be expected for organic nitrogen, phosphorus, and bacteria.

Sorption of pollutants to soils is probably the most significant fate mechanism of toxicants in biofiltration devices. Many of the devices also use sedimentation and filtration to remove the particulate forms of the pollutants from the water. Incorporation of the pollutants onto soil with subsequent biodegradation and minimal leaching to the groundwater is desired. Volatilization, photolysis, biotransformation, and bioconcentration may also be significant in grass filter strips and grass swales. Underground seepage drains and porous pavements offer little biological activity to reduce toxicants.

Results and Conclusions

This entire research project will provide guidance on critical source area treatment, especially for the protection of groundwater quality. Much of the information will

also be useful for analyzing stormwater problems and needed controls for surface water discharges.

Table 4 is a summary of the pollutants found in stormwater that may cause groundwater contamination problems for various reasons. This table does not consider the risk associated with using groundwater contaminated with these pollutants. Causes of concern include high mobility (low sorption potential) in the vadose zone, high abundance (high concentrations and high detection frequencies) in stormwater, and high soluble fractions (small fraction associated with particulates that would have little removal potential using conventional stormwater sedimentation controls) in the stormwater. The contamination potential is the lowest rating of the influencing factors. As an example, when no pretreatment is used before percolation through surface soils, the mobility and abundance criteria are most important. When a compound is mobile but in low abundance (such as for volatile organic compounds, VOCs), then the groundwater contamination potential would be low. When the compound is mobile, however, and also in high abundance (such as for sodium chloride, in certain conditions), then the groundwater contamination potential would be high. When sedimentation pretreatment is to be used before infiltration, then some of the pollutants will likely be removed before infiltration. In this case, all three influencing factors (pollutant mobility, pollutant abundance in stormwater, and fraction of the pollutant associated with the filtered sample fraction) would be considered. As an example, chlordane would have a low contamination potential with sedimentation pretreatment, whereas it would have a moderate contamination potential when no pretreatment is used. In addition, when subsurface infiltration/injection is used instead of surface percolation, the compounds would most likely be more mobile, making the abundance criteria the most important, with some regard given to the filterable fraction information for operational considerations.

This table is only appropriate for initial estimates of contamination potential because of the simplifying assumptions made, such as the worst case mobility conditions assumed (for sandy soils having low organic content). When the soil is clayey and has a high organic content, then most of the organic compounds would be less mobile than that shown on this table. The abundance and filterable fraction information is generally applicable for warm weather stormwater runoff in residential and commercial areas. The pollutant concentrations and detection

frequencies, however, would be greater for critical source areas (especially vehicle service areas) and critical land uses (especially manufacturing industrial areas).

The stormwater pollutants of most concern (those that may have the greatest adverse impacts on groundwaters) include:

- Nutrients: nitrate has a low to moderate potential for contaminating groundwater when both surface percolation and subsurface infiltration/injection are used because of its relatively low concentrations in most stormwaters. When the stormwater nitrate concentration is high, then the groundwater contamination potential would likely also be high.
- Pesticides: lindane and chlordane have moderate potentials for contaminating groundwater when surface percolation (with no pretreatment) or when subsurface injection (with minimal pretreatment) are used. The groundwater contamination potentials for both of these compounds would very likely be substantially reduced with adequate sedimentation pretreatment.
- Other organics: 1,3-dichlorobenzene may have a high potential for contaminating groundwater when subsurface infiltration/injection (with minimal pretreatment) is used. It would, however, probably have a lower groundwater contamination potential for most surface percolation practices because of its relatively strong sorption to vadose zone soils. Both pyrene and fluoranthene would also very likely have high groundwater contamination potentials for subsurface infiltration/injection practices, but lower contamination potentials for surface percolation practices because of their more limited mobility through the unsaturated zone (vadose zone). Others (including benzo(a)anthracene, bis(2-ethylhexyl) phthalate, pentachlorophenol, and phenanthrene) may also have moderate groundwater contamination potentials when surface percolation with no pretreatment, or subsurface injection/infiltration, is used. These compounds would have low groundwater contamination potentials when surface infiltration is used with sedimentation pretreatment. VOCs may also have high groundwater contamination potentials if present in the stormwater (which is possible for some industrial and commercial facilities and vehicle service estab-

lishments).

- Pathogens: enteroviruses very likely have high potentials for contaminating groundwater when any percolation or subsurface infiltration/injection practice is used, depending on their presence in stormwater (especially if contaminated with sanitary sewage). Other pathogens, including *Shigella*, *Pseudomonas aeruginosa*, and various protozoa, would also have high groundwater contamination potentials when subsurface infiltration/injection practices are used without disinfection. When disinfection (especially by chlorine or ozone) is used, then disinfection by-products (such as trihalomethanes or ozonated bromides) would have high groundwater contamination potentials.
- Heavy Metals: nickel and zinc possibly have high potentials for contaminating groundwater when subsurface infiltration/injection is used. Chromium and lead would have moderate groundwater contamination potentials for subsurface infiltration/injection practices. All metals would possibly have low groundwater contamination potentials when surface infiltration is used with sedimentation pretreatment.
- Salts: chloride would very likely have a high potential for contaminating groundwater in northern areas where road salts are used for traffic safety, irrespective of the pretreatment, infiltration, or percolation practices used.

Pesticides have been mostly found in urban runoff from residential areas, especially in dry weather flows associated with landscaping irrigation runoff. The other organics, especially the volatiles, are mostly found in industrial areas. The phthalates are found in all areas. The PAHs are also found in runoff from all areas, but they are in higher concentrations and occur more frequently in industrial areas. Pathogens are most likely associated with sanitary sewage contamination of storm drainage systems, but several bacterial pathogens are commonly found in surface runoff in residential areas. Zinc is mostly found in roof runoff and other areas where galvanized metal comes into contact with rainwater. Salts are at their greatest concentrations in snowmelt and early spring runoff in northern areas.

The control of these compounds requires various approaches, including source area controls, end-of-pipe controls, and pollution prevention. All dry weather flows should be diverted from infiltration

devices because of their potentially high concentrations of soluble heavy metals, pesticides, and pathogens. Similarly, all runoff from manufacturing industrial areas should also be diverted from infiltration devices because of their relatively high concentrations of soluble toxicants. Combined sewer overflows should also be diverted because of sewage contamination. In areas of snow and ice control, winter snowmelt and runoff and early spring runoff should also be diverted from infiltration devices.

All other runoff should include pretreatment using sedimentation processes before infiltration, to both minimize groundwater contamination and to prolong the life of the infiltration device (if needed). This pretreatment can take the form of grass filters, sediment sumps, wet detention ponds, etc., depending on the runoff volume to be treated, treatment flow rate, and other site specific factors. Pollution prevention can also play an important role in minimizing groundwater contamination problems, including reducing the use of galvanized metals, pesticides, and fertilizers in critical areas. The use of specialized treatment devices, such as those being developed and tested during this research, can also play an important role in treating runoff from critical source areas before these more contaminated flows commingle with cleaner runoff from other areas. Sophisticated treatment schemes, especially the use of chemical processes or disinfection, may not be warranted, except in special cases, especially when the potential of forming harmful treatment by-products (such as THMs and soluble aluminum) is considered.

The use of surface percolation devices (such as grass swales and percolation ponds) that have a substantial depth of underlying soils above the groundwater is preferable to the use of subsurface infiltration devices (such as dry wells, trenches or seepage drains, and especially injection wells), unless the runoff water is known to be relatively free of pollutants. Surface devices are able to take greater advantage of natural soil pollutant removal processes. Unless all percolation devices are carefully designed and maintained, however, they may not function properly and may lead to premature hydraulic failure or contamination of the groundwater.

Recommendations

With a reasonable degree of site-specific design considerations to compensate for soil characteristics, infiltration may be

Table 4. Potential of Stormwater Pollutants to Contaminate Groundwater

Compounds		Mobility (sandy/low organic soils)	Abundance in Stormwater	Fraction Filterable	Surface Infiltr. and No Pretreatment	Contamination Potential Surface Infiltr. with Sedimentation	Sub-surface Inj. with Minimal Pretreatment
Nutrients	nitrates	mobile	low/moderate	high	low/moderate	low/moderate	low/moderate
Pesticides	2,4-D	mobile	low	likely low	low	low	low
	γ-BHC (lindane)	intermediate	moderate	likely low	moderate	low	moderate
	malathion	mobile	low	likely low	low	low	low
	atrazine	mobile	low	likely low	low	low	low
	chlordane	intermediate	moderate	very low	moderate	low	moderate
	diazinon	mobile	low	likely low	low	low	low
Other organics	VOCs	mobile	low	very high	low	low	low
	1,3-dichloro-benzene	low	high	high	low	low	high
	anthracene	intermediate	low	moderate	low	low	low
	benzo(a)anthracene	intermediate	moderate	very low	moderate	low	moderate
	bis (2-ethylhexyl) phthalate	intermediate	moderate	likely low	moderate	low	moderate
	butyl benzyl phthalate	low	low/moderate	moderate	low	low	low/moderate
	fluoranthene	intermediate	high	high	moderate	moderate	high
	fluorene	intermediate	low	likely low	low	low	low
	naphthalene	low/inter.	low	moderate	low	low	low
	pentachlorophenol	intermediate	moderate	likely low	moderate	low	moderate
	phenanthrene	intermediate	moderate	very low	moderate	low	moderate
	pyrene	intermediate	high	high	moderate	moderate	high
	Pathogens	enteroviruses	mobile	likely present	high	high	high
Shigella		low/inter.	likely present	moderate	low/moderate	low/moderate	high
Pseudomonas aeruginosa protozoa		low/inter. low/inter.	very high likely present	moderate moderate	low/moderate low/moderate	low/moderate low/moderate	high high
Heavy metals	nickel	low	high	low	low	low	high
	cadmium	low	low	moderate	low	low	low
	chromium	inter./very low	moderate	very low	low/moderate	low	moderate
	lead	very low	moderate	very low	low	low	moderate
	zinc	low/very low	high	high	low	low	high
Salts	chloride	mobile	seasonally high	high	high	high	high

very effective in controlling both urban runoff quality and quantity problems. This strategy encourages infiltration of urban runoff to replace the natural infiltration capacity lost through urbanization and to use the natural filtering and sorption capacity of soils to remove pollutants; however, the potential for some types of urban runoff to contaminate groundwater through infiltration requires some restrictions. Infiltration of urban runoff having potentially high concentrations of pollutants that may pollute groundwater requires adequate pretreatment or the diversion of these waters away from infiltration devices. The following general guidelines for the infiltration of stormwater and other storm drainage effluent are recommended in the absence of comprehensive site-specific evaluations:

- Dry weather storm drainage effluent should be diverted from infiltration devices because of their probable high concentrations of soluble heavy metals, pesticides, and pathogenic microorganisms.
- Combined sewage overflows should be diverted from infiltration devices because of their poor water quality, especially their high pathogenic microorganism concentrations and high clogging potential.
- Snowmelt runoff should be diverted from infiltration devices because of its potential for having high concentrations of soluble salts.
- Runoff from manufacturing industrial areas should be diverted from infiltration devices because of its potential

- for having high concentrations of soluble toxicants.
- Construction site runoff must be diverted from stormwater infiltration devices (especially subsurface devices) because of its high suspended solids concentrations, which would quickly clog infiltration devices.
- Runoff from other critical source areas, such as vehicle service facilities and large parking areas, should at least receive adequate pretreatment to eliminate their groundwater contamination potential before infiltration.
- Runoff from residential areas (the largest component of urban runoff in most cities) is generally the least polluted urban runoff flow and should be considered for infiltration. Very little treat-

ment of residential area stormwater runoff should be needed before infiltration, especially if surface infiltration is through the use of grass swales. When subsurface infiltration (seepage drains, infiltration trenches, dry wells, etc.) is used, then some pretreatment may be needed, such as by using grass filter strips, or other surface filtration devices.

Recommended Stormwater Quality Monitoring to Evaluate Potential Groundwater Contamination

Most past stormwater quality monitoring efforts have not adequately evaluated stormwater's potential for contaminating groundwater. The following list shows the stormwater contaminants that are recommended for monitoring when stormwater contamination potential needs to be considered, or when infiltration devices are to

be used. Other analyses are appropriate for additional monitoring objectives (such as evaluating surface water problems). In addition, all phases of urban runoff should be sampled, including stormwater runoff, dry-weather flows, and snowmelts.

- Urban runoff contaminates with the potential to adversely affect groundwater:
 - Nutrients (especially nitrates)
 - Salts (especially chloride)
 - VOCs (if expected in the runoff, such as runoff from manufacturing industrial or vehicle service areas, could screen for VOCs with purgable organic carbon analyses)
 - Pathogens (especially enteroviruses, if possible, along with other pathogens such as *Pseudomonas aeruginosa*, *Shigella*, and pathogenic protozoa)
 - Bromide and total organic carbon (to estimate disinfection by-product

generation potential, if disinfection by either chlorination or ozone is being considered)

- Pesticides, in both filterable and total sample components (especially lindane and chlordane)
- Other organics, in both filterable and total sample components (especially 1,3 dichlorobenzene, pyrene, fluoranthene, benzo(a)anthracene, bis (2-ethylhexyl) phthalate, pentachlorophenol, and phenanthrene)
- Heavy metals, in both filterable and total sample components (especially chromium, lead, nickel, and zinc)
- Urban runoff compounds with the potential to adversely affect infiltration and injection operations:
 - Sodium, calcium, and magnesium (to calculate the sodium adsorption ratio to predict clogging of clay soils)
 - Suspended solids (to determine the need for sedimentation pretreatment to prevent clogging)

Robert Pitt, Shirley Clark and Keith Parmer are with the Department of Civil and Environmental Engineering, the University of Alabama at Birmingham, Birmingham, AL 35294

Richard Field is the EPA Project Officer (see below).

The complete report, entitled "Potential Groundwater Contamination from Intentional and Nonintentional Stormwater Infiltration," (Order No. PB94-165354AS; Cost: \$27.00, subject to change) will be available only from:

*National Technical Information Service
5285 Port Royal Road
Springfield, VA 22161
Telephone: 703-487-4650*

*The EPA Project Officer can be contacted at:
Risk Reduction Engineering Laboratory
U.S. Environmental Protection Agency
Edison, NJ 08837-3679*

United States
Environmental Protection Agency
Center for Environmental Research Information
Cincinnati, OH 45268

Official Business
Penalty for Private Use
\$300

EPA/600/SR-94/051

BULK RATE
POSTAGE & FEES PAID
EPA
PERMIT No. G-35